

## **µAME17 PC** MICROMETRIC FORCE ACTUATOR

DATA SHEET ISP ISP23D091FP00007-V1

MAJ: 05/04/2024



Non contractual picture

# $\mu AME$ 17\_PC actuator has an astatic design, it generates bidirectional forces with a very high resolution.

#### 1 - Description

- Its patented design is cost effective and robust.
- The system is driven by a stepper motor. It permits a stable and constant force application without power supply thanks to its irreversible mechanics.
- The output rod with its floating head allows angular and radial misalignments without generating any parasitic torque not friction.
- The actuator can be customized upon customer request

#### 2 – Possible applications

- Mirror deformation for wavefront correction
- Application of forces with high resolution
- Static actuator with controlled force

### 3 – Technical specifications

		Up to 4N/s
Supply voltage	24V	Working temperature :
Nominal current	0.5 A rms/phase	20 to 22 °C
Specifications:		Actuator mass:
Force resolution	0.5 mN/step	About 60 g
Force range	± 17 N	Options:
Linearity (after calibration)	0,1%	<ul> <li>Dedicated connector</li> </ul>
Hysteresis	1%	Controller
Repeatability	0.01 N RMS	Interface for fixation to a mirror
Accuracy (after calibration)	0.02 N RMS	
outy ratio:		
ccording to application, Pleas	e ask.	
Ø 11.8 g6		91.7 mid stroke lengt
M13 x1 thread	<u>11,8</u> <u>11,8</u>	
<u>11</u> <u>9.8</u>	11,8 • • • • • • • • • • • • • • • • • • •	5 62 33 44 44 <b>@</b> www.isp-system.fr
11 9.8 Ø 10 V Ø 10 Ø 10 Ø 10 Ø 10 Ø 10 Ø 10 Ø 10 Ø 10	+33 (0)	

This document belongs to ISP SYSTEM, it cannot be used, copied or communicated without a prior written agreement. The mentioned information, herein, are subject to change. Thanks to consult ISP SYSTEM