

Update : 01/08/2014



Photos non contractuelles

Ce chariot est destiné à transporter et à stocker un fantôme PET avec une radioprotection équivalente à 25 mm de plomb.

1 - Technical data

- Chassis with inox rectangular frame 316L, brush finish
- 4 high diameter wheels (200mm) with hard tyre, both are swivel and braked
- Large handle to release the brake
- Shielded vessel with steel double jacket in which the lead is confined with a coat of white epoxy paint.

Thickness of the shield

- Top and 3 side faces 23 mm de lead + 2 x 3 mm of steel (equivalent to 25 mm of lead)
- Door: 20 mm lead + 13mm steel (equivalent to 25mm of lead)).
- Bottom: 10 mm of lead + 13 mm of steel (equivalent of 15 mm of lead)
- Closing ensure by 2 clips. A latch hook allow to pre-lock the door closing
- Stainless still spill containment tray of 13L, located under the phantom and extractable by the side, in case of leak
- 2 provided blocks on polypropylene adapted to the dimensions of both phantom allow to block them and center them on their support on top of the spill containment tray.
- Dimension : 1330 x 660 x 1010 mm (Lx l x H)
- Mass: 399 kg

 **ISP SYSTEM**
Z.I. de la Herray
65500 VIC-EN-BIGORRE – France

 +33 (0)5 62 33 44 44
 contact@isp-system.fr

 www.isp-system.fr

Capital de 1 000 000 € - SIRET : 410 675 078 00027 – APE : 71128 – TVA : FR 19 410 675 078